

Agilent Technologies
Corporate Legal Department
1601 California Avenue, M/S 17L-5A
Palo Alto, California 94304 USA
650/485-2386
FAX 650/485-5487



Agilent Technologies

FAX RECEIVED

JUN 14 2002

GROUP 1600

Fax Cover Sheet

OFFICIAL

To:	Tina Plunkett, Patent Specialist	From:	Gordon Stewart Fax # 650/485-5487
Company:	US Patent & Trademark Ofc.	Date:	June 13, 2002
Telephonic Number:	703-305-3524	Number of pages following:	25
Fax Number:	703-308-4556	If you have problems with this fax transmission please contact:	Elizabeth Miller 650/485-4125

MESSAGE: RE: US Application No. 09/359,527, Filed July 22, 1999
Attorney Docket No. 10990641-1

Attached, per our phone conversation of June 12, 2002, are the documents for the above-referenced US application which were originally faxed to Examiner Arden Marschel, Tech Center #1600 on March 25, 2002, in response to the outstanding Office Action mailed October 23, 2001. The PTO confirmation sheet is included.

Warning: This message is intended only for the use of the individual or entity to which it is addressed and may contain information that is privileged, confidential, and exempt from disclosure under applicable law. If you are not the intended recipient, you are hereby notified that any use, dissemination, distribution, or copying of this communication is strictly prohibited. If you have received this communication in error, please notify us immediately by telephone, and return this original message to us at the above address via the U.S. Postal Service. Thank you.

03/26/02 18:28:07

USPTO->

650 485 5487 FAX

Page 001

TO:Aut -reply fax to 650 485 5487 COMPANY:

Auto-Reply Facsimile Transmission**UNITED STATES
PATENT AND
TRADEMARK OFFICE**

TO:

Fax Sender at 650 485 5487

Fax Information

Date Received:

3/25/02 7:14:54 PM [Eastern Standard Time]

Total Pages:

24 (including cover page)

ADVISORY: This is an automatically generated return receipt confirmation of the facsimile transmission received by the Office. Please check to make sure that the number of pages listed as received in Total Pages above matches what was intended to be sent. Applicants are advised to retain this receipt in the unlikely event that proof of this facsimile transmission is necessary. Applicants are also advised to use the certificate of facsimile transmission procedures set forth in 37 CFR 1.8(a) and (b), 37 CFR 1.6(f). Trademark Applicants, also see the Trademark Manual of Examining Procedure (TMEP) section 702.04 et seq.

Received
Cover
Page
=====>

SENT BY: AGILENT TP 1 FAX PAID AUTO RPT; 650 485 5487; MAR-25-02 18:10; PAGE 1

Agilent Technologies
 Agilent Technologies
 Corporate Legal Department
 1401 California Avenue, NW 170-4A
 Palo Alto, California 94304 USA
 6504855487
 FAX 650485-5487

Fax Cover Sheet

TO:	Examiner Arden Marchel Tech Center #1600	FROM:	Gordon Stewart Fax # 650/485-5487
COMMITTEE:	US Patent & Trademark Ofc.	DATE:	March 25, 2002
TELEPHONE NUMBER:	703-300-3994	NUMBER OF PAGES FOLLOWING:	23
FAX NUMBER:	703-872-9306	IF YOU HAVE PROBLEMS WITH THIS FAX TRANSMISSION PLEASE CONTACT:	Elizabeth Miller 650485-4125

MESSAGE: RE: US Application No. 09/359,527, Filed July 23, 1999
 Attorney Docket No. 10890641-1

Accompanying this are the following documents for the subject patent application:

1. Transmittal Letter for Responses/Amendments, and 1 copy
2. Petition for Extension of Time
3. Response and Amendment, 20 pages

CONFIDENTIALITY NOTICE:
 I hereby certify that this document is being transmitted to the Patent and Trademark Office via the USPTO's secure system.

Elizabeth Miller March 25, 2002
 Director

Warning: This message is intended only for the individual or entity to which it is addressed and may contain information that is confidential, privileged, and exempt from disclosure under applicable law. If you are not the intended recipient, you are hereby notified that any use, distribution, disclosure, or copying of this communication is strictly prohibited. If you have received this communication in error, please notify us immediately by e-mail, and return this original message to us at the phone number via the U.S. Postal Service. Thank you.

Received from 650 485 5487 at 3/25/02 7:14:54 PM [Eastern Standard Time]

Agilent Technologies
Corporate Legal Department
1601 California Avenue, M/S 17L-5A
Palo Alto, California 94304 USA
650/485-2386
FAX 650/485-5487



Agilent Technologies

Fax Cover Sheet

To:	Examiner Arden Marschel Tech Center #1600	From:	Gordon Stewart Fax # 650/485-5487
Company:	US Patent & Trademark Ofc.	Date:	March 25, 2002
Telephone Number:	703-308-3894	Number of pages following:	23
Fax Number:	703-872-9306	If you have problems with this fax transmission please contact:	Elizabeth Miller 650/485-4125

MESSAGE: RE: US Application No. 09/359,527, Filed July 22, 1999
Attorney Docket No. 10990641-1

Accompanying this are the following documents for the subject patent application:

1. Transmittal Letter for Response/Amendment, and 1 copy
2. Petition for Extension of Time
3. Response and Amendment, 20 pages

CERTIFICATE OF FILING BY ELECTRONIC FACSIMILE TRANSMISSION

I hereby certify that this document is being facsimile transmitted to the Patent and Trademark Office on the date shown below.


Elizabeth Miller

March 25, 2002
Date

Warning: This message is intended only for the use of the individual or entity to which it is addressed and may contain information that is privileged, confidential, and exempt from disclosure under applicable law. If you are not the intended recipient, you are hereby notified that any use, dissemination, distribution, or copying of this communication is strictly prohibited. If you have received this communication in error, please notify us immediately by telephone, and return this original message to us at the above address via the U.S. Postal Service. Thank you.

AGILENT TECHNOLOGIES, INC.
Legal Department, DL425
Intellectual Property Administration
P. O. Box 7599
Loveland, Colorado 80537-0599

PATENT APPLICATION

ATTORNEY DOCKET NO. 10990641-1

IN THE
UNITED STATES PATENT AND TRADEMARK OFFICE

Inventor(s): Peter G. Webb et al.

Serial No.: 09/359,527

Examiner: Arden Marschel

Filing Date: July 22, 1999

Group Art Unit: 1631

Title: BIOPOLYMER ARRAYS AND THEIR FABRICATION

OFFICIAL

FAX RECEIVED

JUN 14 2002

GROUP 1600

COMMISSIONER FOR PATENTS
Washington, D.C. 20231

TRANSMITTAL LETTER FOR RESPONSE/AMENDMENT

Sir:

Transmitted herewith is/are the following in the above-identified application:

- (X) Response/Amendment (X) Petition to extend time to respond
() New fee as calculated below () Supplemental Declaration
() No additional fee (Address envelope to "Box Non-Fee Amendments")
() Other: _____ (fee \$ _____)

CLAIMS AS AMENDED BY OTHER THAN A SMALL ENTITY						
(1) FOR	(2) CLAIMS REMAINING AFTER AMENDMENT	(3) NUMBER EXTRA	(4) HIGHEST NUMBER PREVIOUSLY PAID FOR	(5) PRESENT EXTRA	(6) RATE	(7) ADDITIONAL FEES
TOTAL CLAIMS	19	MINUS	45	= 0	X \$18	\$ 0
INDEP. CLAIMS	5	MINUS	8	= 0	X \$84	\$ 0
[] FIRST PRESENTATION OF A MULTIPLE DEPENDENT CLAIM					+ \$280	\$ 0
EXTENSION FEE	1ST MONTH \$110.00	2ND MONTH \$400.00	3RD MONTH \$920.00	4TH MONTH \$1440.00		\$ 400
		X				
OTHER FEES						\$
TOTAL ADDITIONAL FEE FOR THIS AMENDMENT						\$ 400

Charge \$ 400 to Deposit Account 50-1078. At any time during the pendency of this application, please charge any fees required or credit any overpayment to Deposit Account 50-1078 pursuant to 37 CFR 1.25. Additionally please charge any fees to Deposit Account 50-1078 under 37 CFR 1.16, 1.17, 1.19, 1.20 and 1.21. A duplicate copy of this sheet is enclosed.

I hereby certify that this paper is being facsimile transmitted to the Patent and Trademark Office on the date shown below.

Date of Facsimile: March 25, 2002

Typed Name: Elizabeth Miller

Signature: Elizabeth Miller

Respectfully submitted,

Peter G. Webb et al.

By Gordon M. Stewart

Gordon M. Stewart

Attorney/Agent for Applicant(s)
Reg. No. 3,528

Date: March 25, 2002

CERTIFICATE OF FILING BY ELECTRONIC FACSIMILE TRANSMISSION

I hereby certify that this document is being facsimile transmitted to the Patent and Trademark Office on the date shown below.

Elizabeth Miller
Elizabeth MillerMarch 25, 2002
Date

#13/c

ATTORNEY DOCKET NO. 10990641-1

Plunkett
6/20/02IN THE UNITED STATES PATENT AND TRADEMARK OFFICEIn re Application of: Peter G. Webb *et al.*

Group Art Unit: 1631

Serial No.: 09/359,527

Examiner: Arden Marschel
(formerly Jeffrey Lundgren)

Filed: 07/22/99

Title: BIOPOLYMER ARRAYS AND THEIR FABRICATION

Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

AMENDMENT AND RESPONSE

Please amend the present application by canceling claims 1, 7, 15, 16, 18, 19, 46-48 and amending other of the claims as indicated in the attached APPENDIX. In accordance with 37 CFR 1.121(c)(3) a clean copy of all of the claims as now pending is below:

2. (AMENDED) A method according to claim 10, additionally comprising operating the deposition apparatus according to the corrected drive pattern.

3. (AMENDED) A method according to claim 10 wherein the probes are DNA or RNA probes.

4. (AMENDED) A method according to claim 10 additionally comprising saving the target drive pattern in a memory of the deposition apparatus.

28

US Application No. 09/359,527

Attorney Docket No. 10990641-1

Page 2

Sup D2
5. (AMENDED) A method according to claim 10 additionally comprising saving the target drive pattern in a memory of the deposition apparatus, and wherein the corrected drive pattern is saved in the memory.

C1
6. (AMENDED) A method according to claim 10 wherein the corrected drive pattern is derived without obtaining a target drive pattern.

C2
Sub D3
8. (TWICE AMENDED) A method of fabricating an addressable array of biopolymer probes on a substrate according to a target array pattern using a deposition apparatus which, when operated according to a target drive pattern based on nominal operating parameters of the apparatus, provides the probes on the substrate in the target array pattern, the method comprising:

- (a) examining at least one operating parameter for an error from a nominal value which error will result in use of the target drive pattern producing a discrepancy between the target array pattern and an actual array pattern deposited;
- (b) when an error is detected deriving, based on the error, a corrected drive pattern different from the target drive pattern such that use of the corrected drive pattern results in a reduced discrepancy between the target and actual array patterns; and
- (c) operating the deposition apparatus according to the corrected drive pattern so as to fabricate the array;

wherein:

the deposition apparatus includes a dispensing head to dispense fluid droplets containing the probes or probe precursors, and a transport system to move at least one of the dispensing head and substrate relative to the other as the droplets are dispensed from the head, so as to form the array;

the target drive pattern controls operation of the transport system; and

the operating parameter is the position of the dispensing head, which is examined by viewing the dispensing head.

C3
13
12
9. (AMENDED) A method according to claim 8 wherein the operating parameter is examined by viewing a fiducial mark on the dispensing head.

US Application No. 09/359,527

Attorney Docket No. 10990641-1
Page 3

Sub 24
10. (AMENDED) A method of fabricating an addressable array of biopolymer probes on a substrate according to a target array pattern using a deposition apparatus which, when operated according to a target drive pattern based on nominal operating parameters of the apparatus, provides the probes on the substrate in the target array pattern, the method comprising:

- (a) examining at least one operating parameter for an error from a nominal value which error will result in use of the target drive pattern producing a discrepancy between the target array pattern and an actual array pattern deposited;
- (b) when an error is detected deriving, based on the error, a corrected drive pattern different from the target drive pattern such that use of the corrected drive pattern results in a reduced discrepancy between the target and actual array patterns; and
- (c) operating the deposition apparatus according to the corrected drive pattern so as to fabricate the array;

wherein:

the deposition apparatus includes a dispensing head with multiple nozzles to dispense fluid droplets containing the probes or probe precursors, and a transport system to move at least one of the dispensing head and substrate relative to the other as the droplets are dispensed from the head, so as to form the array;

the drive pattern controls operation of the transport system;

C3
the at least one operating parameter is the position of the substrate or dispensing head, or orientation of a nozzle, and is examined by viewing the dispensing head, or nozzle, or a droplet pattern previously dispensed from the head.

C4 sub 24
11. (AMENDED) A method according to claim 4 additionally comprising saving the target drive pattern in a memory of the deposition apparatus, and wherein the corrected drive pattern is saved in the memory, prior to operating the dispensing head and transport system to form the array.

12. (AMENDED) A method according to claim 4 additionally comprising saving the target drive pattern in a memory of the deposition apparatus, and wherein the corrected drive pattern is derived by modifying, based on the detected error, instructions to at least one deposition apparatus component based on the target drive

C

US Application No. 09/359,527

Attorney Docket No. 10990641-1
Page 4

pattern during operation of the dispensing head and transport system to form the array.

13. (AMENDED) A method according to claim 10 wherein the at least one operating parameter is examined by viewing the droplet pattern previously dispensed from the head.

14. (AMENDED) A method according to claim 10 wherein the at least one operating parameter is a position of the dispensing head.

17. (AMENDED) A method of fabricating an addressable array of biopolymer probes on a substrate according to a target array pattern using a deposition apparatus which, when operated according to a target drive pattern based on nominal operating parameters of the apparatus, provides the probes on the substrate in the target array pattern, the method comprising:

- (a) examining at least one operating parameter for an error from a nominal value which error will result in use of the target drive pattern producing a discrepancy between the target array pattern and an actual array pattern deposited;
- (b) when an error is detected deriving, based on the error, a corrected drive pattern different from the target drive pattern such that use of the corrected drive pattern results in a reduced discrepancy between the target and actual array patterns; and
- (c) operating the deposition apparatus according to the corrected drive pattern so as to fabricate the array;

wherein:

the deposition apparatus includes a dispensing head with multiple nozzles to dispense fluid droplets containing the probes or probe precursors, and a transport system to move at least one of the dispensing head and substrate relative to the other as the droplets are dispensed from the head, so as to form the array;

the drive pattern controls operation of the transport system;

and wherein the at least one parameter is a position of a nozzle which is examined by viewing the nozzle, or a droplet pattern previously dispensed from the head.

US Application No. 09/359,527

Attorney Docket No. 10990641-1

Page 5

C6
Sub
D6

49. (AMENDED) A method of fabricating an addressable array of biopolymer probes on a substrate according to a target array pattern using a deposition apparatus which, when operated according to a target drive pattern based on nominal operating parameters of the apparatus, provides the probes on the substrate in the target array pattern, the method comprising:

- (a) examining at least one operating parameter for an error from a nominal value which error will result in use of the target drive pattern producing a discrepancy between the target array pattern and an actual array pattern deposited;
- (b) when an error is detected deriving, based on the error, a corrected drive pattern different from the target drive pattern such that use of the corrected drive pattern results in a reduced discrepancy between the target and actual array patterns; and
- (c) operating the deposition apparatus according to the corrected drive pattern so as to fabricate the array;

wherein the operating parameter is a fluid volume dispensed by the deposition apparatus.

C7
Sub
D6

50. (AMENDED) A method of fabricating an addressable array of biopolymer probes on a substrate according to a target array pattern using a deposition apparatus which, when operated according to a target drive pattern based on nominal operating parameters of the apparatus, provides the probes on the substrate in the target array pattern, the method comprising:

- (a) examining at least one operating parameter for an error from a nominal value which error will result in use of the target drive pattern producing a discrepancy between the target array pattern and an actual array pattern deposited;
- (b) when an error is detected deriving, based on the error, a corrected drive pattern different from the target drive pattern such that use of the corrected drive pattern results in a reduced discrepancy between the target and actual array patterns; and
- (c) operating the deposition apparatus according to the corrected drive pattern so as to fabricate the array;

wherein the operating parameter is a position of a component which varies due to thermal expansion.

US Application No. 09/359,527

Attorney Docket No. 10990641-1

Page 6

CS
SUP
D6

51. (AMENDED) A method of fabricating an addressable array of biopolymer probes on a substrate according to a target array pattern using a deposition apparatus which, when operated according to a target drive pattern based on nominal operating parameters of the apparatus, provides the probes on the substrate in the target array pattern, the method comprising:

- (a) examining at least one operating parameter for an error from a nominal value which error will result in use of the target drive pattern producing a discrepancy between the target array pattern and an actual array pattern deposited;
- (b) when an error is detected deriving, based on the error, a corrected drive pattern different from the target drive pattern such that use of the corrected drive pattern results in a reduced discrepancy between the target and actual array patterns; and
- (c) operating the deposition apparatus according to the corrected drive pattern so as to fabricate the array;

wherein:

the deposition apparatus includes a dispensing head to dispense fluid droplets containing the probes or probe precursors, and a transport system to move at least one of the dispensing head and substrate relative to the other as the droplets are dispensed from the head, so as to form the array;

the apparatus further includes an encoder to provide data on the location of the substrate or head; and

the at least one operating parameter is an encoder error.

52. (AMENDED) A method of fabricating an addressable array of biopolymer probes on a substrate according to a target array pattern using a deposition apparatus which, when operated according to a target drive pattern based on nominal operating parameters of the apparatus, provides the probes on the substrate in the target array pattern, the method comprising:

- (a) examining at least one operating parameter for an error from a nominal value which error will result in use of the target drive pattern producing a discrepancy between the target array pattern and an actual array pattern deposited;

US Application No. 09/359,527

Attorney Docket No. 10990641-1

Page 7

- (b) when an error is detected deriving, based on the error, a corrected drive pattern different from the target drive pattern such that use of the corrected drive pattern results in a reduced discrepancy between the target and actual array patterns; and
- (c) operating the deposition apparatus according to the corrected drive pattern so as to fabricate the array;
- wherein:

the deposition apparatus includes a dispensing head with multiple nozzles to dispense fluid droplets containing the probes or probe precursors, and a transport system to move at least one of the dispensing head and substrate relative to the other as the droplets are dispensed from the head, so as to form the array;

the drive pattern controls operation of the transport system;

the operating parameter is the position of the dispensing head, or orientation of a nozzle, and is examined by viewing the dispensing head, or nozzle.

C8
SUP
DN
55. A method according to claim 49 wherein the deposition apparatus comprises multiple jets for dispensing droplets, and wherein the corrected drive pattern comprises an instruction to switch to a different jet when a deviation from nominal volume is encountered for one jet which is more than a predetermined tolerance.

C9
SUB
DN
56. (AMENDED) A method of fabricating an addressable array of biopolymer probes on a substrate according to a target array pattern using a deposition apparatus which, when operated according to a target drive pattern based on nominal operating parameters of the apparatus, provides the probes on the substrate in the target array pattern, the method comprising:

- (a) examining at least one operating parameter for an error from a nominal value which error will result in use of the target drive pattern producing a discrepancy between the target array pattern and an actual array pattern deposited;
- (b) when an error is detected deriving, based on the error, a corrected drive pattern different from the target drive pattern such that use of the corrected drive pattern results in a reduced discrepancy between the target and actual array patterns; and
- (c) operating the deposition apparatus according to the corrected drive pattern so as to fabricate the array;
- C